

## Your Device Will Always Be At Their Best

The power station can recharge itself by fast PD 3.1 type-C Port. And charge up to 6 devices at once. (drones, Macbook, cameras etc.) equipped with:

**\*One AC outlet \*1 USB-C port(Input/ouput supported)**

**\*1 USB-C 3.1 ports \*2 USB-A port \*1 DC Port**



# Go 300

## Product Parameters

General Info	Model	Gendome Go 300(Power Station)
	Capacity	288Wh
	Certificate	FCC,UL,UN38.3,CE,RoHS,WEEE,METI,PSE

Output	AC Output	Max 300w,120V 60Hz
	USB-C Port(*1,PD3.1)	Max 140W, 5V $\Rightarrow$ 3A/9V $\Rightarrow$ 3A/12V $\Rightarrow$ 3A/15V $\Rightarrow$ 3A/20V $\Rightarrow$ 5A/28V $\Rightarrow$ 5A
	USB-A Port(*2,QC3.0)	Max 18W, 5V $\Rightarrow$ 3A/9V $\Rightarrow$ 2A/12V $\Rightarrow$ 1.5A
	Wireless Output(*1)	Max 15W

INput	USB-C Port(*1,PD3.1)	Max 140W, 5V $\Rightarrow$ 3A/9V $\Rightarrow$ 2A/12V $\Rightarrow$ 1.5A
	Solar Charge	Max 120W

Battery Info	Cell Chemistry	EV-Proven LiFePO4
	LEP	5 Years Of Use
	BMS Protection	Over Voltage Protection, Overload Protection, Over Temperature Protection, Short Circuit Protection, Low Temperature Protection, Low Voltage Protection, Over Current Protection.
	Ambient Temp.for Discharging	32-113°F / 0-45°C
	Ambient Temp.for Charging	32-113°F / 0-45°C
	Optimal Operating Temp.	68-86°F / 20-30°C
Ambient Temp.for Storage	32-113°F / 0-45°C	

Smart Control	Connection	Bluetooth, Wi-Fi
	App	Gendome App
	Firmware Update	OTA(Over-the-air) Update
	Display	LCD Screen
	Other Functions	Amazon Alexa,Google Home Connectivity